

## Softswim Filter Cleaner Quart



**Brand:** Bioguard

**Product Code:** 22859BIO

**Availability:** In Stock

**Weight:** 0.00oz

**Dimensions:** 0.00ft x 0.00ft x 0.00ft

**Price: \$21.99**

### Description

1 Quart - Softswim Filter Cleaner

### What it does

Specially designed to clean filters for SoftSwim<sup>®</sup> pools.

### Features

- Phosphoric acid 5-10%\*
- Hydrochloric acid <5%
- pH <2
- Effectively cleans all filter types
- Designed especially for use with SoftSwim<sup>®</sup> systems

### Benefits

- Cleans filter media to allow more effective filtration
- Helps keep water clear by promoting better filtration

*\*The exact percentage (concentration) of composition has been withheld as a trade secret*

## **Directions for Use**

### **Sand and Most D.E. Filters**

1. Backwash thoroughly. Turn pump off.
2. For most effective results, remove lid from lint pot and pour 1 quart of this product into the pot.
  - If this is not possible, pour the product into the skimmer closest to the filter.
3. With filter in backwash position, turn pump on for 5-10 seconds or until a slight pink color is seen in site glass or filter discharge.
4. Turn pump off and turn valve to the closed position, if available. Let filter cleaner soak for 12-24 hours before backwashing.
5. Backwash filter for at least 2 minutes or until site glass or filter discharge water is clear of color, dirt, and debris.
6. Rinse and return to normal operation.

### **Non Backwashable D.E. and Cartridge Filter**

1. Turn pump off.
2. Remove elements from filter and rinse off debris with a high pressure hose.
3. Immerse completely and soak 12-24 hours in a clean plastic bucket containing 1 quart of this product in 5 gallons of water for small filter elements or 2 quarts of this product in 10 gallons of water for large filter elements.
4. Clean and rinse thoroughly with water using a high pressure hose.
5. Replace elements and resume normal operation.
  - For best performance, allow D.E. filter septum or cartridge element to completely dry before replacement.