

Kleen-it Filter Cleaner



Brand: Bioguard

Product Code: 23758BIO

Availability: In Stock

Weight: 0.00oz

Dimensions: 0.00ft x 0.00ft x 0.00ft

Price: \$20.99

Description

1 Quart - Kleen-it Filter Cleaner

What it does

Kleen It[®] removes metals, dirt and scale from DE, cartridge and sand filters. This means lower maintenance costs, longer filter cycles, cleaner water, and better filtration. Kleen It[®] can also be used to clean spa surfaces, outdoor furniture, pool equipment, vinyl, plastic and rubber surfaces.

Features

- pH 1.0
- Compatible with chlorine, bromine, Mineral Springs and saltwater systems
- Not recommended for use on filters for SoftSwim[®] or other biguanide systems
- Compatible with all filter types

Benefits

- Removes metals, dirt, and scale from filter
- Keeps filter working at optimum performance
- Cleans sand, D.E., and Cartridge filters
- Soak or spray application
- Fresh citrus scent

Directions for Use

Directions for Use

Non-Backwashable D.E. & Cartridge Filters

1. Turn pump off and rinse off loose dirt from filter elements.
2. Apply product by spraying directly onto filter elements. If needed, lightly brush heavy grease spots.
3. Let wet filter elements soak for 5–10 minutes. For heavily soiled filters, allow elements to soak for 1 hour.
4. Rinse elements thoroughly with full-strength water from a garden hose.
5. Reassemble filter and resume normal operation.
 - As an alternative, soak filter elements overnight into a solution of 32 oz. of this product added to 5 gallons of water. Rinse elements thoroughly with full-strength water from a garden hose.
6. Once the cartridge is clean, it is best to let the filter cartridges air-dry before using them again.

Sand & some D.E. Filters

1. Backwash filter thoroughly. Turn pump off.
2. Chlorinating product must be removed from the skimmer basket prior to addition of product.
 - Automatic feeder should be turned off prior to any addition of this product.
3. Pour entire bottle of Kleen It[®] into skimmer.
4. Turn pump on until pump primes and product moves into filter.
5. Turn pump off. Leave filter selector in backwash position or in closed position.
6. Wait 1 hour. Turn pump on with selector in backwash position, and backwash until waste water is clear.